

# Injector Performance Table

## Water Suction Capacity

REV 2014

Operating Pressure PSIG		Model 283 ½" Threads		Model 287 ½" Threads		Model 384 ½" Threads		Model 384X ½" Threads		Model 484 ½" & ¾" Threads		Model 484X ¾" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH
5	0	0.17	3.2	0.29	5.2	0.71	10.3	0.71	11.7	1.2	14.6	1.2	23.5
	1		2.0		2.6		8.7		8.6		10.4		16.6
	2		1.1		1.8		7.4		4.0		6.6		11.9
	3				1.2		5.0						7.3
	4		*(3.5)		*(3.5)		*(3.9)		*(2.9)		*(4.4)		*(3.5)
10	0	0.24	4.7	0.32	6.2	1.0	15.3	1.0	17.5	1.7	18.7	1.7	29.7
	2		2.8		4.8		11.5		13.5		13.9		23.0
	5		1.2		1.9		7.6		2.0		6.0		11.8
	7				0.8		2.0				2.7		3.7
	8		*(7.0)		*(7.7)		*(8.2)		*(6.6)		*(8.4)		*(7.5)
15	0	0.28	5.4	0.42	6.8	1.2	13.3	1.2	27.7	2.1	18.7	2.1	38.6
	5		2.7		4.1		11.3		11.7		11.4		20.9
	7		1.7		2.9		8.4		4.1		8.2		15.6
	10				1.3		4.8						
	12		*(10.5)		*(11.5)		*(12.9)		*(9.6)		*(12.5)		*(8.7)
20	0	0.32	5.8	0.51	7.0	1.4	13.0	1.4	29.6	2.4	18.0	2.4	39.5
	5		3.7		6.1		13.1		17.1		15.6		27.6
	10		2.0		3.4		9.2		3.0		9.4		13.3
	12		0.6		1.9		6.3				7.7		8.4
	15		*(15.0)		*(16.0)		*(16.5)		*(12.4)		*(17.0)		*(13.2)
25	0	0.35	5.9	0.57	7.8	1.6	14.1	1.6	33.1	2.7	17.8	2.7	39.5
	5		4.8		6.9		14.2		22.4		17.2		32.1
	10		2.6		4.4		12.7		11.2		13.7		22.0
	15		0.7		2.3		6.6				7.4		9.9
	20		*(18.5)		*(19.5)		*(20.5)		*(15.0)		*(21.6)		*(16.5)
30	0	0.39	6.0	0.65	8.0	1.7	14.1	1.7	33.8	2.9	17.2	2.9	39.7
	5		5.8		7.9		14.4		24.6		17.0		38.1
	10		3.8		5.6		13.8		17.3		16.6		28.8
	15		2.4		3.6		10.7		6.9		11.2		17.0
	20		0.8		1.7		4.5				7.0		
25	*(22.5)	*(24.5)	*(25.2)	*(18.0)	*(25.5)	*(17.2)							
35	0	0.41	6.0	0.70	8.1	1.9	14.4	1.9	33.7	3.1	17.3	3.1	40.3
	5		6.0		8.0		14.4		29.0		17.3		39.3
	10		4.8		6.8		14.4		19.1		17.3		33.8
	15		3.4		5.0		13.7		10.7		17.3		24.2
	20		1.7		3.0		9.4				11.1		14.7
25	*(26.0)	*(27.0)	*(28.6)	*(20.8)	*(29.5)	*(23.5)							
40	0	0.43	6.0	0.75	8.1	2.0	14.1	2.0	33.9	3.4	17.1	3.4	40.8
	5		6.0		8.1		14.1		31.5		17.7		38.6
	10		5.5		7.4		13.9		24.1		17.7		38.5
	15		4.2		6.3		13.9		14.2		17.7		29.9
	20		2.6		4.3		12.6		3.5		15.2		20.6
25	1.2	2.7	7.5		11.4	6.5							
30	*(29.5)	*(31.0)	*(32.0)	*(22.8)	*(33.3)	*(26.1)							
45	0	0.46	6.0	0.81	8.1	2.1	13.7	2.1	33.9	3.6	17.2	3.6	41.4
	5		6.0		8.1		13.7		31.6		17.2		39.0
	10		5.8		8.1		13.7		30.7		17.4		37.9
	15		4.9		6.9		13.7		18.9		17.4		34.9
	20		3.4		5.5		13.7		11.0		16.7		26.9
25	2.7	4.0	12.1	1.4	13.8	18.2							
30	1.0	2.4	6.1		10.2								
35	*(33.5)	*(35.0)	*(36.1)	*(26.1)	*(36.8)	*(25.4)							
50	0	0.48	6.0	0.85	8.3	2.2	14.1	2.2	33.8	3.8	17.4	3.8	41.6
	5		6.0		8.3		14.1		32.7		17.4		40.4
	10		6.0		8.3		14.1		31.7		17.7		39.1
	15		5.7		8.0		14.1		25.3		17.7		37.3
	20		4.7		5.9		13.5		15.2		17.7		29.4
25	3.5	4.5	13.5	6.7	16.4	20.2							
30	2.1	3.0	10.1		12.7								
35	0.7	1.2	6.0		7.7								
40	*(37.0)	*(39.0)	*(39.6)	*(28.7)	*(41.0)	*(29.0)							

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright© 2015

Mazzei Injector Company, LLC  
500 Rooster Drive, Bakersfield, CA 93307-9555 USA

[www.mazzei.net](http://www.mazzei.net)

# Injector Performance Table

## Water Suction Capacity

REV 2014

Operating Pressure PSIG		Model 283 ½" Threads		Model 287 ½" Threads		Model 384 ½" Threads		Model 384X ½" Threads		Model 484 ½" & ¾" Threads		Model 484X ¾" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH
60	0	0.54	6.0	0.92	8.3	2.5	13.7	2.5	34.3	4.1	17.7	4.1	42.4
	5		6.0		8.3		13.7		34.2		17.7		42.2
	10		6.0		7.8		13.5		34.0		17.7		38.3
	15		6.0		7.8		13.5		31.9		17.6		38.0
	20		5.7		7.8		13.4		24.1		17.6		37.5
	30		3.8		5.7		12.3		9.1		17.2		23.1
	35		2.4		4.1		11.6		1.5		15.2		
	40		1.3		2.7		8.3				12.0		
	45		*(45.5)				0.7		*(47.3)		2.4		*(35.4)
70	0	0.58	6.0	0.99	8.3	2.6	12.1	2.6	35.1	4.5	18.0	4.5	42.3
	5		6.0		8.3		12.1		35.8		18.0		42.5
	10		6.0		8.3		12.2		34.7		17.1		39.5
	15		6.0		8.3		12.1		32.9		17.1		37.2
	20		6.0		8.3		12.2		30.7		17.1		35.6
	30		5.2		7.4		12.2		17.9		17.1		31.3
	40		2.9		4.7		11.9		3.4		16.2		16.3
	45		1.9		3.5		11.0				13.4		
	50		0.9		1.7		7.5				11.3		
55	*(54.0)		*(55.0)	*(52.4)		*(41.5)		*(58.5)		*(40.7)			
80	0	0.60	6.0	1.1	8.3	2.8	11.7	2.8	34.5	4.8	16.9	4.8	42.3
	5		6.0		8.3		11.7		34.2		16.9		41.9
	10		6.0		8.3		11.6		34.6		16.9		41.8
	15		6.0		8.3		11.7		32.9		16.9		40.7
	20		6.0		8.3		11.7		31.6		16.1		40.7
	30		6.0		8.1		11.6		26.3		16.2		39.7
	40		4.5		6.4		11.6		11.7		15.7		26.9
	50		2.3		4.1		11.2				14.9		6.8
	60				0.9		6.8				6.1		
65	*(60.5)		*(63.0)	*(61.9)		*(47.2)		*(66.0)		*(51.9)			
90	0	0.65	6.0	1.1	8.3	3.0	11.1	3.0	34.8	5.1	13.6	5.1	42.2
	5		6.0		8.3		11.1		34.2		13.6		41.9
	10		6.0		8.3		11.1		34.4		13.6		40.7
	20		6.0		8.3		11.1		32.9		13.6		40.7
	30		6.0		8.3		11.1		29.6		13.6		39.4
	40		5.7		7.9		11.1		18.4		13.6		33.4
	50		3.5		5.7		11.1		4.8		13.6		26.3
	60		1.6		3.5		11.0				13.3		
	70				0.2		4.6				4.2		
75	*(68.0)		*(71.0)	*(71.0)		*(53.1)		*(74.0)		*(54.3)			
100	0	0.69	6.0	1.2	7.7	3.2	10.8	3.2	33.5	5.3	13.2	5.3	42.4
	5		6.0		7.7		11.0		33.0		13.2		41.9
	10		6.0		7.7		10.8		32.6		13.2		40.7
	20		6.0		7.7		11.0		31.8		13.2		39.6
	30		6.0		7.7		11.0		31.6		13.2		40.7
	40		6.0		7.4		10.8		29.3		13.2		34.9
	50		5.0		7.2		11.0		12.2		13.1		27.0
	60		3.0		5.2		11.0				13.3		
	70		1.2		3.0		10.4				12.8		
80	*(76.0)		*(79.0)	*(78.6)		*(59.0)		*(82.9)		*(59.7)			
120	0	0.76	6.0	1.3	6.4	3.5	10.8	3.5	33.9	5.8	12.3	5.8	45.8
	5		6.0		6.4		10.8		33.6		12.3		43.8
	10		6.0		6.4		10.8		33.1		12.3		43.2
	20		6.0		6.4		10.8		31.7		12.3		41.9
	30		6.0		6.4		10.8		30.5		12.3		40.1
	40		6.0		6.4		10.8		30.5		12.2		36.8
	50		5.6		6.1		10.8		25.1		12.2		32.0
	60		5.2		5.8		10.8		13.9		12.2		24.8
	70		3.9		4.8		10.8		2.1		12.1		20.3
	80		2.3		3.7		10.8				12.1		
	90		1.0		1.5		8.6				11.7		
100	*(93.0)		*(95.0)	*(96.8)		*(71.3)		*(99.7)		*(71.2)			

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright © 2015

Mazzei Injector Company, LLC  
 500 Rooster Drive, Bakersfield, CA 93307-9555 USA

[www.mazzei.net](http://www.mazzei.net)

# Injector Performance Table

## Water Suction Capacity REV 2014

Operating Pressure PSIG		Model 584 ½" & ¾" Threads		Model 684 ¾" Threads		Model 878-03 1" Threads		Model 885X-03 1" Threads		Model 1078-03 1" Threads		Model 1583 1½" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH
5	0	2.1	29.1	3.5	27.4	3.6	62.8	3.6	78.0	5.5	101	10.7	135
	1		28.9		20.2		36.1		62.5		46.4		84.4
	2		28.4		13.8		23.8		42.7		22.1		53.2
	3		25.3		6.6		7.3		15.5		2.7		
	4		*(4.4)		9.9		*(4.3)		5.6		*(4.1)		1.6
10	0	3.0	28.2	5.0	27.2	5.2	93.7	5.0	115	7.7	105	15.2	219
	2		28.1		27.3		61.9		90.7		75.6		143
	5		27.4		18.4		36.4		44.7		41.7		78.7
	7		13.2		10.8		15.8		19.4		19.1		42.0
	8		*(9.0)		10.9		*(8.5)		6.0		*(8.7)		3.7
15	0	3.6	28.1	6.1	26.1	6.3	87.3	6.2	135	9.5	101	18.6	225
	5		27.9		26.1		62.1		83.1		79.9		163
	7		28.0		25.0		45.4		58.0		64.6		124
	10		13.9		12.8		23.6		19.1		34.2		86.5
	12		*(13.5)		11.0		*(13.0)		7.0		*(12.5)		7.2
20	0	4.2	24.8	7.0	25.1	7.3	82.8	7.1	141	10.9	98.2	21.4	228
	5		24.8		25.2		80.4		117		95.4		205
	10		23.7		25.2		48.6		57.6		69.9		143
	12		19.1		18.4		33.6		36.1		51.5		131
	15		*(18.0)		14.5		*(16.5)		10.4		*(16.5)		21.0
25	0	4.7	25.1	7.8	24.8	8.2	82.3	8.0	142	12.2	95.9	24.0	226
	5		25.2		24.8		81.3		135		96.6		226
	10		25.1		24.9		73.2		96.5		89.4		193
	15		20.8		24.3		45.3		38.4		68.1		148
	20		*(22.0)		12.1		*(21.0)		5.1		*(21.0)		20.1
30	0	5.1	25.3	8.6	24.5	8.9	79.9	8.7	144	13.4	94.3	26.3	226
	5		25.3		24.6		79.1		140		94.4		226
	10		24.9		24.6		76.9		125		94.4		211
	15		25.1		24.5		65.3		69.3		82.0		167
	20		18.2		14.7		35.3		14.3		55.4		125
25	*(27.0)	11.5	*(26.0)	6.7	*(26.1)	9.0	*(20.5)	*(26.0)	*(26.0)	18.3			
35	0	5.5	25.5	9.3	24.7	9.7	79.3	9.4	142	14.5	93.9	28.4	226
	5		25.5		24.6		79.3		141		93.9		226
	10		25.4		24.7		77.5		135		93.9		224
	15		25.2		24.7		74.5		106		91.8		205
	20		21.9		24.9		52.3		54.1		74.1		164
25	*(31.5)	16.5	*(29.5)	12.9	*(30.1)	30.2	*(24.0)	*(30.0)	*(29.4)	89.0			
40	0	5.9	25.6	9.9	24.9	10.3	77.4	10.1	140	15.5	93.1	30.3	227
	5		25.5		25.0		77.4		141		93.1		228
	10		25.6		25.1		77.4		139		93.1		227
	15		25.5		25.0		77.4		128		93.1		220
	20		25.2		25.0		73.6		90.4		91.8		192
25	21.3	24.7	50.6	36.8	72.2	153							
30	*(35.5)	15.0	*(35.0)	10.8	*(34.4)	28.2	*(27.0)	*(34.4)	*(33.4)	81.4			
45	0	6.3	25.8	10.5	25.0	11.0	79.6	10.7	140	16.4	92.8	32.2	227
	5		25.9		25.0		79.6		139		92.8		228
	10		25.9		25.0		79.6		139		92.8		227
	15		25.8		25.0		79.6		134		92.8		223
	20		25.7		25.0		78.8		112		93.8		212
25	23.5	25.1	67.0	74.4	86.9	174							
30	19.4	20.6	44.1	23.1	66.1	113							
35	*(40.0)	13.5	*(37.5)	8.4	*(38.4)	22.0	*(31.0)	*(38.7)	*(37.5)	47.1			
50	0	6.6	25.5	11.1	25.0	11.5	74.7	11.3	139	17.3	92.4	33.9	227
	5		25.5		24.9		74.7		140		92.4		227
	10		25.5		24.9		74.7		140		92.4		226
	15		25.5		25.0		74.7		139		92.4		225
	20		25.4		24.9		74.7		128		92.4		224
25	24.4	24.9	68.3	106	92.3	203							
30	21.5	17.1	56.1		86.3	172							
35	15.7	9.1	36.6		64.3	120							
40	*(45.0)	2.8	*(42.0)	6.7	*(42.3)	9.5	*(36.0)	*(43.9)	*(41.9)	40.4			

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright © 2015

Mazzei Injector Company, LLC  
500 Rooster Drive, Bakersfield, CA 93307-9555 USA

www.mazzei.net

# Injector Performance Table

## Water Suction Capacity

REV 2014

Operating Pressure PSIG		Model 584 ½" & ¾" Threads		Model 684 ¾" Threads		Model 878-03 1" Threads		Model 885X-03 1" Threads		Model 1078-03 1" Threads		Model 1583 1½" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH
60	0	7.2	26.4	12.1	25.1	12.6	72.4	12.3	140	19.0	92.7	37.2	229
	5		26.4		25.0		72.4		140		92.7		228
	10		26.3		25.3		72.4		140		92.7		229
	15		26.3		25.3		72.4		140		92.7		226
	20		26.2		25.2		72.4		138		92.7		227
	30		25.3		25.2		71.2		110		93.0		206
	35		23.8		25.1		63.3		73.3		91.7		182
	40		20.0		13.4		41.4		33.2		77.1		147
	45		*(53.5)		14.4		*(50.0)		7.0		*(51.2)		16.3
70	0	7.8	25.8	13.1	25.4	13.7	73.6	13.3	141	20.5	93.3	40.1	228
	5		25.8		25.3		73.6		141		93.3		228
	10		25.9		25.5		73.6		140		93.3		228
	15		25.9		25.4		73.6		140		93.3		228
	20		25.8		25.5		73.6		140		93.3		228
	30		25.6		25.4		73.6		135		93.4		225
	40		25.6		25.4		67.5		87.6		92.3		198
	45		23.3		20.7		46.9		44.5		81.8		159
	50		16.7		10.5		30.7				54.5		124
55	*(63.0)	9.0	*(58.3)	6.9	*(58.3)	12.9	*(51.0)	*(58.9)	28.7	*(56.7)	43.2		
80	0	8.4	26.2	14.0	25.5	14.6	74.2	14.2	139	21.9	93.8	42.9	231
	5		26.2		25.5		74.2		139		93.8		231
	10		26.2		25.5		74.2		140		93.8		231
	15		26.2		25.6		74.2		139		93.8		231
	20		26.3		25.6		74.2		140		93.8		231
	30		26.2		25.6		74.2		139		93.8		231
	40		26.3		25.6		73.7		124		94.7		220
	50		25.0		25.6		56.9		60.0		91.5		177
	60		17.1		15.6		25.8				52.8		93.1
65	*(72.5)	7.8	*(67.0)	5.0	*(67.5)	7.9	*(57.0)	*(68.5)	33.0	*(70.1)	11.9		
90	0	8.9	27.0	14.9	25.7	15.5	74.2	15.1	141	23.2	94.4	45.5	229
	5		27.0		25.8		74.2		139		94.4		229
	10		27.0		25.7		74.2		141		94.4		229
	20		27.4		25.8		74.2		139		94.4		229
	30		27.2		25.8		74.2		140		94.4		229
	40		27.2		25.8		74.2		136		95.6		229
	50		27.2		25.8		70.0		103		94.3		217
	60		24.4		25.8		47.8		34.7		84.6		177
	70		13.2		25.7		18.1				39.5		49.0
75	*(80.5)	5.2	*(76.0)	13.3	*(75.6)	0.84	*(66.0)	*(76.9)	20.5	*(73.1)			
100	0	9.3	28.7	15.7	23.5	16.3	76.3	15.9	141	24.5	94.1	48.0	232
	5		28.7		24.2		76.3		141		94.1		232
	10		28.7		24.2		76.3		141		94.1		232
	20		29.2		23.9		76.3		141		94.1		232
	30		29.0		23.9		76.3		140		94.1		232
	40		28.8		23.9		76.3		139		94.1		232
	50		28.8		23.9		74.5		130		93.9		228
	60		28.4		23.9		67.7		87.7		94.9		206
	70		23.3		24.0		44.6		32.5		81.3		146
80	*(90.0)	16.8	*(85.0)	21.5	*(84.5)	13.0	*(73.0)	*(86.0)	30.6	*(81.3)	25.7		
120	0	10.2	32.1	17.2	24.5	17.9	75.3	17.4	140	26.8	94.4		
	5		32.1		24.9		75.3		140		94.4		
	10		32.1		24.6		75.3		140		94.4		
	20		32.1		24.6		75.3		140		94.4		
	30		32.1		24.7		75.3		140		94.4		
	40		31.8		24.5		75.3		140		94.4		
	50		31.8		24.4		75.3		135		94.4		
	60		31.6		24.7		74.9		131		95.2		
	70		31.6		24.5		70.2		84.6		94.4		
	80		28.6		21.7		61.2		28.0		90.8		
	90		17.1		19.4		34.5				61.2		
100	*(107)		*(102)	18.1	*(101)	8.5	*(85.0)	*(102)	22.3				

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright © 2015

Mazzei Injector Company, LLC  
 500 Rooster Drive, Bakersfield, CA 93307-9555 USA

[www.mazzei.net](http://www.mazzei.net)

# Injector Performance Table

## Water Suction Capacity

REV 2014

Operating Pressure PSIG		Model 1585X 1½" Threads		Model 1587 1½" Threads		Model 2081 2" Threads		Model 2083X 2" Threads		Model 3090 3" Threads		Model 4091 4" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH
<b>5</b>	0	<b>10.7</b>	123	<b>17.7</b>	244	<b>32.4</b>	629	<b>8.4</b>	456	<b>76.4</b>	1,050	<b>170</b>	2,100
	1		74.7		102		629		157		900		1,500
	2		26.3		91.4		629				758		1,200
	3				54.2		214				456		840
	4		*(3.5)				**(4.1)		135		*(1.4)		
<b>10</b>	0	<b>15.2</b>	241	<b>25.0</b>	269	<b>45.8</b>	629	<b>13.1</b>	560	<b>108</b>	1,446	<b>214</b>	2,820
	2		155		249		629		154		1,448		2,820
	5		43.3		103		467				872		1,860
	7				58.3		149				396		780
	8		*(6.5)				**(8.7)		30.0		*(2.4)		
<b>15</b>	0	<b>18.6</b>	262	<b>30.6</b>	270	<b>56.2</b>	630	<b>16.1</b>	671	<b>132</b>	1,434	<b>251</b>	2,820
	5		157		184		623				1,428		2,820
	7		86.5		154		576				1,042		2,280
	10				98.5		213				554		720
	12		*(9.4)				**(13.5)		76		*(3.7)		
<b>20</b>	0	<b>21.4</b>	308	<b>35.4</b>	267	<b>64.8</b>	630	<b>18.9</b>	757	<b>153</b>	1,416	<b>272</b>	2,820
	5		231		265		630		236		1,416		2,820
	10		120		174		468				1,170		2,700
	12		39.3		142		298				792		1,800
	15		*(12.7)				**(17.0)		151		*(5.7)		
<b>25</b>	0	<b>24.0</b>	324	<b>39.6</b>	265	<b>72.5</b>	630	<b>21.8</b>	811	<b>171</b>	1,344	<b>307</b>	2,820
	5		275		264		630		429		1,340		2,820
	10		204		229		626				1,358		2,820
	15		50.5		156		404				930		1,980
	20		*(15.4)				**(22.1)		134		*(7.1)		
<b>30</b>	0	<b>26.3</b>	323	<b>43.3</b>	263	<b>79.4</b>	630	<b>23.1</b>	849	<b>187</b>	1,308	<b>332</b>	2,820
	5		299		261		630		779		1,310		2,820
	10		251		268		630				1,308		2,820
	15		137		200		511				1,282		2,580
	20				164		341				578		1,380
25	*(19.3)		**(25.6)	33.3	*(8.8)		*(25.5)		*(26.0)	240			
<b>35</b>	0	<b>28.4</b>	326	<b>46.8</b>	285	<b>85.8</b>	630	<b>24.4</b>	853	<b>202</b>	1,290	<b>360</b>	2,820
	5		318		284		630		669		1,290		2,820
	10		286		287		630		288		1,266		2,820
	15		204		251		626				1,188		2,820
	20		66.6		191		459				906		2,640
25	*(22.4)		**(29.0)	143	*(10.4)		*(29.5)		*(30.5)	1,440			
<b>40</b>	0	<b>30.3</b>	324	<b>50.0</b>	287	<b>91.7</b>	630	<b>26.4</b>	897	<b>216</b>	1,254	<b>382</b>	2,820
	5		321		284		630		919		1,254		2,820
	10		307		282		630		388		1,254		2,820
	15		257		278		630				1,256		2,820
	20		146		244		523				1,110		2,820
25	11.9	180	394		712	1,860							
30	*(25.5)		**(33.2)	115	*(11.6)		*(32.5)		*(35.0)	900			
<b>45</b>	0	<b>32.2</b>	326	<b>53.1</b>	259	<b>97.3</b>	630	<b>27.7</b>	947	<b>229</b>	1,260	<b>402</b>	2,820
	5		324		259		630		748		1,260		2,820
	10		318		260		630		485		1,260		2,820
	15		287		257		630				1,258		2,820
	20		210		256		606				1,200		2,820
25	106	225	507		962	2,820							
30		157	341		580	2,400							
35	*(28.7)		**(38.3)	73.5	*(13.4)		*(36.0)		*(38.9)	960			
<b>50</b>	0	<b>33.9</b>	323	<b>55.9</b>	260	<b>102</b>	630	<b>28.6</b>	1,175	<b>241</b>	1,236	<b>416</b>	2,820
	5		319		259		630		1,278		1,236		2,820
	10		315		259		630		578		1,236		2,820
	15		296		258		630				1,236		2,820
	20		251		257		630				1,238		2,820
25	156	252	587		1,194	2,820							
30	45.4	205	452		882	2,640							
35		137	299		499	1,620							
40	*(32.4)		**(41.0)	75.1	*(14.4)		*(40.5)		*(43.1)	360			

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright © 2015

Mazzei Injector Company, LLC  
 500 Rooster Drive, Bakersfield, CA 93307-9555 USA

[www.mazzei.net](http://www.mazzei.net)

# Injector Performance Table

## Water Suction Capacity

REV 2014

Operating Pressure PSIG		Model 1585X 1½" Threads		Model 1587 1½" Threads		Model 2081 2" Threads		Model 2083X 2" Threads		Model 3090 3" Threads		Model 4091 4" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH	Motive Flow GPM	Water Suction GPH
60	0	37.2	319	61.3	275	112	630	31.5	1,350	265	1,242	460	2,820
	5		318		275		630		1,362		1,242		2,820
	10		317		275		630		850		1,242		2,820
	15		307		275		630		520		1,242		2,820
	20		288		275		630				1,244		2,820
	30		174		271		600				1,238		2,820
	35		76.4		259		508				1,126		2,760
	40				212		380				760		2,520
	45		*(38.2)				117		*(50.0)		216		*(17.9)
70	0	40.1	316	66.2	277	121	630	33.8	1,430	286	1,230	495	2,760
	5		316		277		630		1,509		1,230		2,760
	10		316		277		630		1,261		1,230		2,760
	15		312		277		630		719		1,230		2,760
	20		300		277		630		438		1,230		2,760
	30		260		274		630				1,228		2,760
	40		68.2		263		528				1,208		2,760
	45				209		440				1,100		2,760
	50				151		326				720		1,860
55	*(44.7)		58.2	*(58.5)	142	*(20.9)		*(58.5)	402	*(60.5)	960		
80	0	42.9	321	70.8	275	130	630	34.8	1,454	305	1,230	532	2,700
	5		321		275		630		1,519		1,230		2,700
	10		321		275		630		1,396		1,230		2,700
	15		321		275		630		825		1,230		2,700
	20		311		275		630		575		1,230		2,700
	30		287		275		630				1,230		2,700
	40		209		273		604				1,230		2,700
	50				229		505				1,158		2,700
	60				92.5		269				594		1,800
65	*(51.1)		51.4	*(66.5)	60.7	*(24.2)		*(67.5)	300	*(69.5)	840		
90	0	45.5	309	75.1	274	138	630	36.6	1,486	324	1,230	569	2,520
	5		309		274		630		1,526		1,230		2,520
	10		309		274		630		1,481		1,230		2,520
	20		302		274		630		1,085		1,230		2,520
	30		295		274		630		638		1,230		2,520
	40		270		274		630				1,230		2,520
	50		106		272		601				1,232		2,400
	60				208		458				1,090		2,340
	70				62.6		179				466		1,680
75	*(57.5)			*(75.5)		*(31.7)		*(76.5)		*(79.1)	840		
100	0	48.0	305	79.1	275	145	630	39.3	1,447	342	1,230	600	2,520
	5		305		275		630		1,524		1,230		2,520
	10		305		275		630		1,449		1,230		2,520
	20		300		275		630		1,009		1,230		2,520
	30		282		275		630		885		1,230		2,520
	40		273		275		630				1,230		2,520
	50		193		274		621				1,234		2,520
	60		14.6		265		593				1,226		2,520
	70				179		412				942		2,340
80	*(63.2)		62.6	*(83.0)	120	*(33.2)		*(85.0)	376	*(88.6)	900		
120	0			86.7	269	159	630	43.2	1,456				
	5				269		630						
	10				269		630						
	20				269		630						
	30				269		630						
	40				269		630						
	50				269		630						
	60				270		612						
	70				268		595						
	80				226		523						
	90				106		309						
100				*(97.9)		*(100)		*(36.5)					

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright© 2015

 Mazzei Injector Company, LLC  
 500 Rooster Drive, Bakersfield, CA 93307-9555 USA

[www.mazzei.net](http://www.mazzei.net)

# Injector Performance Table

## Air Suction Capacity

REV 2014

Operating Pressure PSIG		Model 287 ½" Threads		Model 384 ½" Threads		Model 484 ½" & ¾" Threads		Model 484X ¾" Threads		Model 584 ½" & ¾" Threads		Model 684 ¾" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH
<b>5</b>	0	<b>0.29</b>	<1.0	<b>0.67</b>	0.60	<b>1.1</b>	5.5	<b>1.1</b>	7.8	<b>2.0</b>	8.8	<b>3.4</b>	9.0
	1		0.19		2.0		2.7		3.2		5.7		
	2				0.35		0.67		1.2		3.0		
	3				0.13		0.48		0.73		1.0		
	4		*(3.5)		*(3.9)		*(4.4)		*(3.5)		*(4.4)		*(4.3)
<b>10</b>	0	<b>0.31</b>	1.0	<b>0.94</b>	3.5	<b>1.6</b>	9.6	<b>1.6</b>	13.1	<b>2.8</b>	14.6	<b>4.7</b>	13.2
	2		<1.0		1.5		3.0		3.9		9.3		
	5				0.34		0.72		1.1		3.6		
	7						0.34		0.38		0.77		1.5
	8		*(7.7)		*(8.2)		*(8.4)		*(7.5)		*(9.0)		*(8.5)
<b>15</b>	0	<b>0.41</b>	2.0	<b>1.2</b>	6.6	<b>2.0</b>	12.6	<b>2.0</b>	17.7	<b>3.5</b>	17.4	<b>5.8</b>	15.4
	5		<1.0		1.0		2.3		2.8		7.2		
	7				0.60		1.3		1.5		4.4		
	10						0.61				0.98		2.1
	12		*(11.5)		*(12.9)		*(12.5)		*(8.7)		*(13.5)		*(13.0)
<b>20</b>	0	<b>0.50</b>	3.0	<b>1.3</b>	8.8	<b>2.3</b>	14.7	<b>2.3</b>	21.4	<b>4.0</b>	20.5	<b>6.7</b>	23.6
	5		<1.0		2.2		4.7		5.3		15.0		
	10				0.64		1.2		1.4		5.7		
	12						0.84		0.99		1.7		3.8
	15		*(16.0)		*(16.5)		*(17.0)		*(13.2)		*(18.0)		*(16.5)
<b>25</b>	0	<b>0.57</b>	3.5	<b>1.5</b>	9.5	<b>2.6</b>	15.7	<b>2.6</b>	24.8	<b>4.5</b>	23.1	<b>7.5</b>	27.5
	5		<1.0		3.0		6.0		8.4		19.6		
	10				1.1		2.0		2.0		8.2		
	15						0.71		1.2		1.9		3.7
	20		*(19.5)		*(20.5)		*(21.6)		*(16.5)		*(22.0)		*(21.0)
<b>30</b>	0	<b>0.63</b>	3.5	<b>1.6</b>	9.9	<b>2.8</b>	16.5	<b>2.8</b>	27.4	<b>4.9</b>	26.1	<b>8.2</b>	30.4
	5		<1.0		3.6		9.0		10.4		23.7		
	10				1.5		3.8		3.3		11.9		
	15				0.77		1.6		1.8		5.9		
	20						0.68				1.8		3.4
25	*(24.5)	*(25.2)	*(25.5)	*(17.2)	*(27.0)	*(26.0)	1.3						
<b>35</b>	0	<b>0.69</b>	4.0	<b>1.8</b>	10.3	<b>3.0</b>	17.5	<b>3.0</b>	30.5	<b>5.3</b>	28.4	<b>8.9</b>	33.0
	5		<1.0		3.8		11.8		14.2		25.9		
	10				1.8		5.4		4.7		16.3		
	15				1.0		2.5		2.3		8.8		
	20				0.57		1.3		1.8		5.5		
25	*(27.0)	*(28.6)	*(29.5)	*(23.5)	*(31.5)	*(29.5)	3.0						
<b>40</b>	0	<b>0.74</b>	4.5	<b>1.9</b>	10.7	<b>3.2</b>	18.1	<b>3.2</b>	32.9	<b>5.7</b>	30.7	<b>9.5</b>	35.0
	5		1.0		4.6		12.6		16.9		27.1		
	10		<1.0		2.2		7.4		7.3		20.9		
	15				1.3		3.6		3.1		11.7		
	20				0.78		1.8		2.4		8.1		
25			1.1		2.7	4.9							
30	*(31.0)	*(32.0)	*(33.3)	*(26.1)	*(35.5)	*(35.0)	3.4						
<b>45</b>	0	<b>0.79</b>	4.5	<b>2.0</b>	11.6	<b>3.4</b>	19.2	<b>3.4</b>	33.0	<b>6.0</b>	31.6	<b>10.1</b>	36.9
	5		2.0		5.5		13.6		19.9		29.9		
	10		<1.0		2.8		8.3		8.9		23.6		
	15				1.6		4.4		4.2		15.4		
	20				1.0		2.8		2.5		9.8		
25		0.70	1.7	2.0	6.5								
30			0.94		2.5	4.0							
35	*(35.0)	*(36.1)	*(36.8)	*(25.4)	*(40.0)	*(37.5)	2.5						
<b>50</b>	0	<b>0.83</b>	4.5	<b>2.1</b>	12.5	<b>3.6</b>	20.7	<b>3.6</b>	33.8	<b>6.3</b>	33.1	<b>10.6</b>	42.0
	5		2.5		6.1		15.2		23.5		33.0		
	10		<1.0		3.4		9.0		11.6		28.4		
	15				1.9		5.1		5.4		19.5		
	20				1.2		3.5		3.3		12.0		
25		0.91	2.7	2.4	8.0								
30			1.4		3.5	5.9							
35			0.87		2.2	3.7							
40	*(39.0)	*(39.6)	*(41.0)	*(29.0)	*(45.0)	*(42.0)	2.0						

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright© 2015

Mazzei Injector Company, LLC  
 500 Rooster Drive, Bakersfield, CA 93307-9555 USA

[www.mazzei.net](http://www.mazzei.net)

# Injector Performance Table

## Air Suction Capacity

REV 2014

Operating Pressure PSIG		Model 287 ½" Threads		Model 384 ½" Threads		Model 484 ½" & ¾" Threads		Model 484X ¾" Threads		Model 584 ½" & ¾" Threads		Model 684 ¾" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH
60	0	0.91	6.0	2.3	13.4	4.0	20.1	4.0	36.6	6.9	36.2	11.6	42.7
	5		<1.0		7.9		17.0		30.3		26.7		34.9
	10		<1.0		4.3		11.7		16.3		21.0		31.5
	15		<1.0		2.8		7.6		10.1		13.6		27.5
	20		<1.0		1.8		5.1		5.2		10.0		17.2
	30		<1.0		0.97		2.4		2.7		5.7		9.3
	35		<1.0		0.56		1.6				4.3		6.8
	40		<1.0				1.2				2.8		5.2
	45		<1.0								2.0		3.2
		*(47.0)		*(47.3)		*(50.7)		*(34.6)		*(53.5)		*(50.0)	
70	0	0.98	7.0	2.5	14.4	4.3	20.7	4.3	39.6	7.5	36.6	12.6	42.9
	5		<1.0		9.6		18.5		31.6		28.8		39.6
	10		<1.0		5.5		14.5		20.9		23.6		35.1
	15		<1.0		3.6		10.1		15.1		17.2		31.4
	20		<1.0		2.4		7.0		7.5		12.8		27.1
	30		<1.0		1.3		3.9		3.7		8.0		13.6
	40		<1.0		0.87		2.2		2.4		4.6		8.1
	45		<1.0				1.6				3.8		5.9
	50		<1.0				1.0				2.7		4.4
55	<1.0				1.7	2.8							
		*(55.0)		*(52.4)		*(58.5)		*(40.7)		*(63.0)		*(58.3)	
80	0	1.0	7.0	2.7	15.9	4.6	21.4	4.6	40.2	8.0	38.0	13.4	42.9
	5		<1.0		11.2		20.0		38.2		31.0		41.8
	10		<1.0		6.6		16.0		28.8		26.2		36.6
	15		<1.0		4.7		11.8		18.3		21.9		34.4
	20		<1.0		3.3		8.5		10.0		16.0		32.1
	30		<1.0		1.8		5.0		5.0		10.4		17.0
	40		<1.0		1.2		3.0		3.1		7.1		10.9
	50		<1.0		0.86		1.6		2.1		4.6		6.6
	60		<1.0				0.92				2.6		4.3
65	<1.0				1.7	3.0							
		*(63.0)		*(61.9)		*(66.0)		*(51.9)		*(72.5)		*(67.0)	
90	0	1.1	7.0	2.8	17.2	4.8	21.9	4.8	42.6	8.5	38.5	14.2	43.1
	5		<1.0		12.8		20.3		39.7		32.7		42.3
	10		<1.0		7.8		17.6		32.9		28.9		39.4
	20		<1.0		4.1		10.2		15.9		19.7		34.3
	30		<1.0		2.3		6.2		7.2		12.9		24.7
	40		<1.0		1.5		4.3		4.5		8.8		14.8
	50		<1.0		1.0		2.7		2.9		5.8		10.1
	60		<1.0		0.81		1.5				3.8		7.1
	70		<1.0				0.88				2.2		4.2
75	<1.0				1.7	2.9							
		*(71.0)		*(71.0)		*(74.0)		*(54.3)		*(80.5)		*(76.0)	
100	0	1.2	7.0	3.0	17.8	5.1	21.9	5.1	44.4	9.0	39.2	15.0	43.6
	5		<1.0		13.9		20.9		42.6		35.2		43.1
	10		<1.0		8.9		18.9		36.6		30.3		42.0
	20		<1.0		4.7		12.2		18.7		23.1		38.1
	30		<1.0		2.7		7.6		10.3		14.4		33.0
	40		<1.0		1.9		5.5		6.0		11.0		18.0
	50		<1.0		1.4		3.5		3.9		7.6		13.1
	60		<1.0		1.0		2.1				5.2		9.5
	70		<1.0		0.78						3.3		6.6
80	<1.0				2.0	3.9							
		*(79.0)		*(78.6)		*(82.9)		*(59.7)		*(90.0)		*(85.0)	
120	0	1.3	7.0	3.3	19.5	5.6	22.8	5.6	48.7	9.8	40.3	16.5	43.8
	5		<1.0		15.3		21.9		47.0		38.4		43.2
	10		<1.0		11.1		21.0		42.6		33.5		42.5
	20		<1.0		6.1		15.3		26.1		27.5		39.8
	30		<1.0		3.8		10.7		15.0		18.5		38.4
	40		<1.0		2.6		7.8		8.4		13.9		27.2
	50		<1.0		2.0		5.9		5.6		10.8		18.1
	60		<1.0		1.5		4.1		4.1		7.6		13.7
	70		<1.0		1.2		2.8		3.0		6.2		10.8
80	<1.0	1.0	2.0		4.3	8.2							
90	<1.0				3.1	5.9							
100	<1.0				1.8	3.7							
		*(95.0)		*(96.8)		*(99.7)		*(71.2)		*(107)		*(102)	

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright© 2015

 Mazzei Injector Company, LLC  
 500 Rooster Drive, Bakersfield, CA 93307-9555 USA

[www.mazzei.net](http://www.mazzei.net)



# Injector Performance Table

## Air Suction Capacity

REV 2014

Operating Pressure PSIG		Model 784 ¾" Threads		Model 878-03 1" Threads		Model 885X-03 1" Threads		Model 978-03 1" Threads		Model 1078-03 1" Threads		Model 1583 1½" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH
5	0	4.3	11.7	3.5	14.9	3.4	18.3	4.1	18.5	5.2	24.3	10.3	39.4
	1		9.8		5.4		9.0		5.1		6.4		17.1
	2		4.7		1.5		1.4		1.8		2.7		3.9
	3		2.1		0.41				0.90		1.5		2.0
	4		*(4.5)		0.99		*(4.1)		*(4.0)		*(3.9)		*(4.0)
10	0	6.1	19.3	4.9	33.9	4.8	26.9	5.7	29.9	7.4	40.1	14.5	85.3
	2		15.6		8.5		15.2		11.2		16.1		25.9
	5		5.7		2.8		1.8		3.1		4.1		8.3
	7		2.0		0.88				1.2		1.5		4.1
	8		*(9.0)		0.93		*(8.7)		*(7.5)		*(9.0)		*(8.1)
15	0	7.5	28.8	6.1	36.0	5.9	38.3	7.0	37.9	9.1	48.6	17.8	114
	5		16.5		7.4		7.9		8.8		13.1		21.7
	7		8.7		3.8		3.4		5.6		7.8		13.9
	10		4.1		0.74				2.4		3.3		6.2
	12		*(13.0)		1.9		*(12.5)		*(11.0)		*(13.4)		*(13.1)
20	0	8.6	33.7	7.0	44.2	6.8	47.1	8.1	44.1	10.5	55.0	20.6	133
	5		21.2		12.5		13.5		14.5		22.1		35.6
	10		8.0		4.3		3.6		6.0		8.5		14.8
	12		4.9		2.7				4.0		5.6		9.4
	15		*(17.5)		2.4		*(16.5)		*(14.0)		*(16.8)		*(17.3)
25	0	9.6	40.0	7.8	44.7	7.6	57.1	9.1	48.0	11.7	60.9	23.0	139
	5		29.1		17.4		27.9		18.7		33.2		48.7
	10		14.0		6.7		7.1		8.6		14.3		23.5
	15		3.3		3.4		2.8		4.6		7.5		11.8
	20		*(22.3)		1.2		*(21.0)		*(17.0)		*(20.8)		*(21.9)
30	0	10.6	48.2	8.6	51.0	8.3	66.9	9.9	49.7	12.9	70.6	25.2	158
	5		32.5		26.1		46.2		26.6		46.4		56.6
	10		20.3		11.3		12.3		12.6		20.5		30.8
	15		9.6		6.4		5.5		7.2		11.2		16.3
	20		4.2		2.9		2.0		3.8		6.1		8.9
25	*(26.5)	2.0	*(26.1)	*(20.5)	*(26.5)	*(26.0)	*(26.0)	6.6					
35	0	11.4	46.4	9.3	51.9	9.0	87.4	10.7	48.2	13.9	74.0	27.2	161
	5		38.1		34.3		27.4		29.1		52.9		68.3
	10		29.7		14.0		16.0		16.2		24.7		36.2
	15		15.2		8.6		7.9		11.0		13.6		22.0
	20		8.2		4.7		4.3		6.8		9.0		13.5
25	*(31.0)	4.0	*(30.1)	*(24.0)	*(30.3)	*(30.0)	*(29.4)	10.2					
40	0	12.2	52.9	9.9	55.8	9.6	80.8	11.5	52.0	14.8	79.8	29.1	173
	5		44.8		40.6		39.2		38.7		57.9		79.2
	10		35.8		17.6		21.3		20.2		31.4		43.4
	15		20.4		11.6		11.2		13.1		18.9		28.4
	20		11.5		6.6		6.8		8.6		13.0		18.8
25	7.1	4.8	4.5	5.5	8.0	12.2							
30	*(34.0)	3.1	*(34.4)	*(27.0)	*(34.3)	*(34.4)	*(33.4)	9.7					
45	0	12.9	56.4	10.5	66.9	10.2	77.1	12.2	54.8	15.7	85.9	30.8	194
	5		48.1		42.1		48.7		42.5		62.8		97.4
	10		38.5		20.7		27.2		23.4		38.3		51.2
	15		29.0		12.8		14.7		16.1		23.2		33.9
	20		14.9		8.9		9.1		11.1		15.7		23.4
25	9.5	5.1	6.5	7.2	11.3	16.2							
30	6.0	4.1	3.5	4.8	7.0	12.9							
35	*(38.0)	2.5	*(38.4)	*(31.0)	*(38.7)	*(38.7)	*(37.5)	9.1					
50	0	13.6	58.1	11.1	64.9	10.7	83.8	12.8	61.1	16.6	87.7	32.5	195
	5		51.9		48.7		49.6		48.3		66.4		109
	10		43.0		23.8		32.2		27.0		42.3		59.0
	15		35.7		16.1		17.7		19.3		25.6		41.4
	20		20.3		10.3		11.2		13.7		16.1		28.2
25	13.6	8.3	7.5	10.0	12.7	18.9							
30	9.2	4.6	4.8	6.8	8.6	13.9							
35	6.0	4.3		4.5	5.3	9.8							
40	*(42.8)	2.8	*(42.3)	*(36.0)	*(42.1)	*(43.9)	*(41.9)	6.7					

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright© 2015

Mazzei Injector Company, LLC  
500 Rooster Drive, Bakersfield, CA 93307-9555 USA

[www.mazzei.net](http://www.mazzei.net)

# Injector Performance Table

## Air Suction Capacity

REV 2014

Operating Pressure PSIG		Model 784 ¾" Threads		Model 878-03 1" Threads		Model 885X-03 1" Threads		Model 978-03 1" Threads		Model 1078-03 1" Threads		Model 1583 1½" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH
60	0	14.9	59.3	12.1	71.3	11.7	120	14.1	73.0	18.2	91.5	35.6	214
	5		57.4		54.9		58.2		57.0		76.3		150
	10		49.4		33.4		45.1		37.3		57.5		75.5
	15		44.1		20.2		23.0		24.7		34.5		52.5
	20		35.0		14.6		16.3		18.1		24.3		39.6
	30		15.5		7.8		8.7		10.7		14.0		20.7
	35		10.4		5.7		6.5		7.9		10.3		16.8
	40		8.0		4.3		3.0		5.6		7.3		11.9
	45		*(50.0)		4.8		*(51.2)		2.4		*(43.0)		*(51.5)
70	0	16.1	59.9	13.1	77.0	12.7	135	15.2	73.6	19.6	100	38.5	241
	5		59.8		60.1		63.5		62.7		81.7		189
	10		54.7		40.7		46.3		49.3		67.5		100
	15		49.6		25.5		29.9		32.0		46.3		67.1
	20		46.3		19.1		22.5		22.9		31.8		47.7
	30		22.3		11.2		12.8		14.9		19.6		27.4
	40		13.5		6.7		7.6		9.2		12.4		18.0
	45		9.8		5.0		5.3		6.9		8.7		12.5
	50		7.5		4.1				4.7		7.0		12.0
55	*(58.3)	4.2	*(58.3)	2.1	*(51.0)	*(60.0)	2.9	*(58.9)	4.5	*(56.7)	11.0		
80	0	17.3	61.0	14.0	81.2	13.5	154	16.2	76.3	21.0	105	41.1	249
	5		60.1		65.0		61.1		67.3		89.6		198
	10		58.0		49.9		55.2		55.9		74.8		108
	15		54.1		31.0		34.2		38.1		57.7		72.4
	20		51.6		23.1		28.7		27.8		39.5		58.8
	30		34.1		14.1		16.2		19.0		24.7		37.5
	40		18.3		9.0		10.1		11.6		17.0		23.8
	50		11.7		5.8		6.2		7.4		10.1		15.0
	60		6.2		3.8				4.0		6.3		12.4
65	*(67.0)	3.5	*(67.5)	2.3	*(57.0)	*(67.5)	3.7	*(68.5)	4.5	*(70.1)	8.8		
90	0	18.3	61.9	14.8	85.3	14.4	168	17.2	87.9	22.3	112	43.6	262
	5		62.0		69.6		68.3		69.8		96.3		208
	10		61.7		56.4		61.6		61.1		81.7		139
	20		56.2		26.9		35.0		33.1		48.8		71.3
	30		48.2		17.3		19.7		22.6		29.4		47.3
	40		25.2		12.1		13.0		16.0		20.8		31.5
	50		16.4		7.9		8.8		9.9		14.9		21.9
	60		11.0		5.1		4.6		7.2		9.1		12.9
	70		5.7		3.4				4.4		5.8		7.1
75	*(76.0)	3.6	*(75.6)	2.1	*(66.0)	*(76.4)	3.6	*(76.9)	4.2	*(73.1)			
100	0	19.3	62.0	15.6	88.6	15.1	184	18.2	90.9	23.5	116	46.0	279
	5		62.8		72.4		73.4		76.1		103		231
	10		61.5		62.8		65.1		67.3		87.7		166
	20		58.3		30.9		42.5		39.0		62.8		80.8
	30		52.6		20.3		24.1		27.7		37.1		55.1
	40		35.7		14.5		15.9		19.2		25.7		38.3
	50		20.8		10.0		11.3		13.3		18.0		26.6
	60		14.5		7.2		7.8		9.7		12.6		19.2
	70		9.6		5.1				6.9		8.3		17.4
80	*(85.0)	4.9	*(84.5)	2.9	*(73.0)	*(85.1)	4.4	*(86.0)	5.5	*(81.3)	13.3		
120	0	21.1	63.3	17.1	98.1	16.6	209	19.9	93.9	25.7	124	50.4	295
	5		63.5		81.0		79.8		81.7		110		248
	10		63.2		70.8		73.2		71.7		97.9		216
	20		62.6		41.9		52.7		48.3		77.7		107
	30		57.2		26.1		28.5		33.4		46.9		71.0
	40		55.0		19.2		21.4		23.9		33.6		53.3
	50		34.4		14.5		16.8		16.0		25.0		39.6
	60		22.6		10.8		11.6		13.4		19.1		29.3
	70		16.6		7.8		9.9		10.0		14.1		20.5
	80		11.8		5.7		3.8		7.7		10.2		19.8
	90		7.3		4.6				5.5		6.7		16.1
100	*(102)		*(101)	2.5	*(85.0)	*(103)	3.9	*(102)	5.1	*(98.4)			

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright © 2015

Mazzei Injector Company, LLC  
 500 Rooster Drive, Bakersfield, CA 93307-9555 USA

[www.mazzei.net](http://www.mazzei.net)

# Injector Performance Table

## Air Suction Capacity REV 2015.12.02

Operating Pressure PSIG		Model 1584 1½" Threads		Model 1585X 1½" Threads		Model 1587 1½" Threads		Model 2081 2" Threads		Model 3090 3" Threads		Model 4091 4" Threads	
Injector INLET	Injector OUTLET	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH
5	0	18.0	47.0	10.3	56.3	17.0	65.9	17.0	17.0	17.0	17.0	146	936
	1		40.0		12.0		21.8						408
	2		31.8		6.9		15.6						156
	3		20.5				8.7						60
	4		*(4.1)		10.6		*(3.5)						*(4.1)
10	0	25.5	98.0	14.5	64.9	24.0	127	43.9	422	103	716	189	1,626
	2		72.4		20.0		61.1		230		635		648
	5		37.1		11.6		21.6		61		379		162
	7		20.5				9.7		48		292		66
	8		*(8.5)		12.6		*(6.5)		*(8.7)		5.0		*(9.0)
15	0	31.2	144	17.8	117	29.4	153	53.8	523	127	985	230	2,436
	5		71.7		18.7		42.6		150		670		420
	7		45.7		11.6		26.7		80		422		234
	10		23.8				13.7		63		262		108
	12		*(13.0)		9.3		*(9.4)		*(13.5)		9.0		*(13.3)
20	0	36.1	170	20.6	130	33.9	173	62.2	606	146	1,138	267	2,772
	5		102		31.1		64.2		244		850		744
	10		41.0		12.7		25.5		88		390		264
	12		31.1		6.4		18.7		79		295		168
	15		*(17.0)		12.6		*(12.7)		*(17.0)		12.0		*(17.5)
25	0	40.3	185	23.0	145	37.9	195	69.5	670	164	1,241	296	3,252
	5		128		48.5		91.0		365		1,001		1,056
	10		65.7		20.2		43.4		137		540		432
	15		33.1		8.0		19.0		88		313		204
	20		*(21.5)		12.0		*(15.4)		*(22.1)		9.8		*(22.3)
30	0	44.2	194	25.2	169	41.5	230	76.1	734	179	1,375	324	3,768
	5		152		60.8		114		468		1,138		1,950
	10		99.4		25.7		54.8		211		679		630
	15		54.3		14.7		30.0		107		385		318
	20		28.5				17.4		89		252		174
25	*(26.0)	10.0	*(19.3)	*(25.6)	10.1	*(26.0)	43	*(25.5)					
35	0	47.7	206	27.2	175	44.9	230	82.2	798	193	1,449	351	3,702
	5		173		78.1		143		559		1,244		2,328
	10		123		34.2		70.8		287		747		768
	15		72.4		20.6		41.6		140		451		474
	20		39.7		10.5		27.0		107		299		270
25	*(30.5)	22.5	*(22.4)	*(29.0)	18.7	*(30.5)	89	*(29.5)	196			144	
40	0	51.0	212	29.1	177	48.0	255	87.9	853	207	1,359	374	4,038
	5		188		87.4		189		634		1,242		2,664
	10		147		45.3		86.8		344		793		960
	15		98.7		24.9		52.4		199		532		624
	20		59.7		16.6		36.2		124		352		402
25	38.4	2.6	26.7	109	246	246							
30	*(35.0)	21.8	*(25.5)	*(33.2)	17.1	*(33.5)	85	*(32.5)	158			132	
45	0	54.1	222	30.8	229	50.9	267	93.2	899	219	1,487	397	4,302
	5		197		105		207		696		1,401		2,868
	10		157		51.1		91.1		433		1,017		1,182
	15		111		32.5		58.8		259		750		738
	20		73.7		21.6		39.9		144		475		522
25	49.7	12.2	28.2	123	345	342							
30	32.4		18.8	109	233	210							
35	*(39.5)	21.2	*(28.7)	*(38.3)	15.1	*(38.0)	80	*(36.0)	30.0				
50	0	57.0	226	32.5	203	53.6	269	98.3	954	231	1,548	419	4,494
	5		207		129		222		761		1,416		3,090
	10		175		56.6		111		519		1,167		1,620
	15		133		38.1		70.6		321		787		852
	20		96.6		27.4		51.7		195		548		648
25	68.3	17.5	37.3	139	426	450							
30	47.0	6.3	22.7	125	305	300							
35	31.8		19.6	109	225	186							
40	*(42.5)	18.5	*(32.4)	*(41.0)	14.4	*(41.5)	74	*(40.5)					

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

# Injector Performance Table

## Air Suction Capacity REV 2015.12.02

Operating Pressure PSIG		Model 1584 1½" Threads		Model 1585X 1½" Threads		Model 1587 1½" Threads		Model 2081 2" Threads		Model 3090 3" Threads		Model 4091 4" Threads		
Injector INLET	Injector OUTLET	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	Motive Flow GPM	Air Suction SCFH	
60	0	62.5	238	35.6	232	58.7	306	108	1,046	253	1,710	455	4,764	
	5		219		182		250		865		1,560		3,480	
	10		190		77.7		161		667		1,294		3,156	
	15		157		51.6		96.0		422		930		1,158	
	20		120		35.6		71.7		301		630		834	
	30		68.3		18.5		40.4		152		415		528	
	35		53.0		10.1		31.9		139		312		378	
	40		37.1				23.3		127		223		258	
	45		25.8				21.8		105		120		168	
	*(51.5)		*(38.2)		*(49.9)		*(50.0)		*(49.0)					
70	0	67.5	244	38.5	261	116		116	1,129	274	1,810	494	4,836	
	5		232		213				955		1,710		3,810	
	10		207		90.3				790		1,518		3,396	
	15		179		59.9				568		1,260		1,602	
	20		150		46.4				405		820		1,074	
	30		91.9		26.9				198		576		708	
	40		56.3		12.2				152		322		420	
	45		43.0						141		252		306	
	50		33.1						125		198		204	
55	21.2			96	90.0	162								
	*(60.0)		*(44.7)		*(58.5)		*(58.5)		*(58.5)					
80	0	72.2	248	41.1	276	124		124	1,202	293	1,980	530	4,878	
	5		239		233				1,031		1,860		4,008	
	10		222		120				894		1,620		3,960	
	15		199		79.3				697		1,350		2,880	
	20		174		59.0				485		1,110		1,266	
	30		117		34.4				281		697		822	
	40		79.7		22.2				175		499		570	
	50		49.0		1.4				153		259		324	
	60		27.8						120		66.0		180	
65	17.9			85	12.0	144								
	*(68.0)		*(51.1)		*(66.5)		*(67.5)		*(67.5)					
90	0	76.5	250	43.6	291	130		130		310	2,100	570	5,040	
	5		246		234						2,040			
	10		234		138						1,920			
	20		193		65.8						1,324			
	30		142		41.9						798			
	40		98.0		27.6						628			
	50		68.3		13.2						457			
	60		46.3								297			
	70		26.5								150			
75	17.9				48.0									
	*(77.0)		*(57.5)				*(76.5)		*(76.5)					
100	0	80.7	252	46.0	318	138		138		327	1,980	627	5,040	
	5		252		250						1,860			
	10		245		188						1,332			
	20		208		76.8						1,216			
	30		168		51.5						757			
	40		122		33.5						594			
	50		89.2		21.8						430			
	60		61.7		7.1						313			
	70		42.4								222			
80	25.2				90.0									
	*(86.0)		*(63.2)				*(85.0)		*(85.0)					
120	0	88.4	260	50.4	337	144		144		345	2,160	720	5,760	
	5		257		262						2,040			
	10		255		234						1,920			
	20		237		100						1,324			
	30		208		64.9						798			
	40		169		46.2						628			
	50		130		35.5						457			
	60		98.7		22.2						297			
	70		75.7		8.3						150			
	80		55.0								48.0			
	90		37.1											
100	21.8													
	*(103)		*(75.3)											

\*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).