



The MAX Series Oxygen Generators are perfect for industrial and commercial applications and delivers 90% purified O₂. Built in a lightweight enclosure and designed with a built-in moisture separator to remove any water vapor before it enters the sieve beds. This allows for increased O₂ purity, and also maximizes the life of the sieve beds.



SYSTEM FEATURES

- Lightweight Powder Coated Aluminum Enclosure
- Low Oxygen Purity & Low-Pressure Alerts
- Built-In Moisture Separator
- Replaceable Cabinet Filters
- Adjustable Flowmeter
- Easily Serviceable

APPLICATIONS

- Glass work/blowing
- Thermal oxidation
- Ozone Gen. feed gas
- Waste Water Treatment
- Environmental Remediation
- Fish Farming
- Hydroponics

Oxidation Technologies, LLC.

214 W Highway 18
Inwood, IA 51240

(515) 635-5854

Sales@oxidationtech.com
www.oxidationtech.com

Model	Oxygen Production	Dimensions (inches LxWxH)	Weight
MAX-5	10.5 SCFH @ 7 PSI	20" x 10" x 24"	56 lbs (26 kg)
MAX-8	16.8 SCFH @ 15 PSI	20" x 10" x 24"	56 lbs (26 kg)
MAX-10	21 SCFH @ 19 PSI	20" x 10" x 24"	56 lbs (26 kg)

PRODUCT CHARACTERISTICS

- Turnkey units with built-in compressors
- Required oxygen concentration is normally obtained within five minutes of the startup of the device
- Oxygen enriched air flow continues for approximately one minute after device shutdown
- Concentration up to 90%
- Temps should remain between 50F (10C) and 105F (40C)



Oxidation Technologies, LLC.
 214 W Highway 18
 Inwood, IA 51240
 (515) 635-5854
 Sales@oxidationtech.com
 www.oxidationtech.com